

## SEL-C285 EIA-232 Serial Cable

Cable for connecting a DTE device to a DCE device with 9-pin female connectors<sup>(1)(2)</sup>

Part Number:

**C 2 8 5 -**

### Length<sup>(3)</sup>

Specify in Feet with Leading Zeros (Example: 5 Feet = 005) Max length 100 Feet

\* Additional Cost

<sup>(1)</sup> To verify your cable application, use the Cable Selector at <https://www.selinc.com/CableSelector/>.

<sup>(2)</sup> Indoor Use Only, CM-Rated

<sup>(3)</sup> The performance of EIA-232 cable lengths greater than 50 feet cannot be guaranteed. As cable lengths increase, so does the risk of interference and equipment damage due to ground potential rise and induced voltages.



9-PIN MALE  
"D" SUB CONNECTOR  
DB-9-P

9-PIN MALE  
"D" SUB CONNECTOR  
DB-9-P

**CABLE:** 9 Conductor 22 AWG 7/30 Tinned Copper with PVC Jacket  
(Shielded: Alpha 1298C or equal)

RXD	2	ORANGE	2
TXD	3	RED	3
GND	5	YELLOW	5
RTS	7	GREEN	7
CTS	8	WHITE	8
SHELL		SHIELD	NO CONNECTION

**Making Electric Power Safer, More Reliable, and More Economical®**

**SEL** SCHWEITZER ENGINEERING LABORATORIES, INC.

2350 NE Hopkins Court - Pullman, WA 99163 USA  
Phone: +1.509.332.1890 - Fax: +1.509.332.7990