SEL-734W Capacitor Bank Controller in Outdoor Enclosure

Standard Features

- **Hardware**
  - Four-Wire Wye Meter Form
  - Three EIA-232 Ports (one for front-panel access)
  - 10/100BASE-T Ethernet Port
  - Conformal Coated Circuit Boards
- **Monitoring**
  - 1 Load Profile Recorder (16 channels)
  - 32 MB
  - 64 Waveform Event Reports
  - 1 kHz Event Capture Sample Rate
  - 15th Order Harmonics
- **Enclosure/Field Interface**
  - Compact (12 in x 10 in) Socket-Based Enclosure
  - Single-Phase Voltage Supply and Measurement, 85-132 Vac
  - Surge Protection Modules
  - Door Switch
- **Protocols**
  - DNP3 Level 2 Outstation Serial and LAN/WAN
  - Modbus RTU/TCP
  - SEL Protocols
- **Other**
  - Instruction Manual on CD

Part Number: **0 7 3 4 0 W 9 F 1 D 1 5 2 6 E X X A D 3 M X X**

Enclosure/Field Interface

Compact (12"x10")/4-Jaw Socket	M

Installed Accessories

Accessory Tray*	A
Integrated 15 Vdc Power Supply for Accessories (40 W) & Accessory Tray*	D

Wireless Sensors

None	X
One*	1
Three*	3

Accessories

Communications Accessories		
	SEL-C662 USB Cable for Computer Terminal (USB, DB9 M/USB A-Type M, Pin 1 Power)*	Please see Online MOT or contact SEL REP or CSR for ordering information.
Enclosure Mounting Accessories		
	Pole Mounting Straps (9.375" - 12.25")*	9159004 48
	Socket-Base Compact Enclosure Locking Ring*	9159003 02

* Additional Cost

Making Electric Power Safer, More Reliable, and More Economical ®

SEL SCHWEITZER ENGINEERING LABORATORIES, INC.
2350 NE Hopkins Court - Pullman, WA 99163 USA
Phone: +1.509.332.1890 - Fax: +1.509.332.7990

Copyright © SEL 2020
All rights reserved.

WI-16325
20200728